

FOR OFFICIAL USE ONLY

		PLUMBING FIXTURE SCHEDULE												
MARK	TYPE	DESCRIPTION	WA	TER		SANITARY								
IVII (I CI C	1111 2	DECORAL FIGH	НОТ	COLD	TRAP	WASTE	VENT							
FCO-90017001	FLOOR CLEANOUT	FLOOR ACCESS HOUSING, DURO-COATED CAST IRON WITH ROUND FRAME AND SCORIATED COVER COMPLETE WITH ADJUSTING SETSCREWS, POLISHED NICKEL BRONZE TOP.				2"								
FCO-90017002	FLOOR CLEANOUT	FLOOR ACCESS HOUSING, DURO-COATED CAST IRON WITH ROUND FRAME AND SCORIATED COVER COMPLETE WITH ADJUSTING SETSCREWS, POLISHED NICKEL BRONZE TOP												
FCO-90017003	FLOOR CLEANOUT	FLOOR ACCESS HOUSING, DURO-COATED CAST IRON WITH ROUND FRAME AND SCORIATED COVER COMPLETE WITH ADJUSTING SETSCREWS, POLISHED NICKEL BRONZE TOP												
FS-90017001	FLOOR SINK	12" SQUARE TOP BY 10" DEEP SANITARY FLOOR SINK WITH WHITE ACID RESISTANT PORCELAIN ENAMEL COATED INTERIOR,. PORCELAIN ENAMEL COATED CAST IRON GRATE, ALUMINUM SEDIMENT BUCKET, CAST IRON PERFORATED GRATE.												
FS-90017002	FLOOR SINK	12" SQUARE TOP BY 10" DEEP SANITARY FLOOR SINK WITH WHITE ACID RESISTANT PORCELAIN ENAMEL COATED INTERIOR,. PORCELAIN ENAMEL COATED CAST IRON GRATE, ALUMINUM SEDIMENT BUCKET, CAST IRON PERFORATED GRATE.												
WCO-90017001	WALL CLEANOUT	ROUND STAINLESS STEEL ACCESS COVER COMPLETE WITH SECURITY SCREW, FOR CAST-IRON WALL CLEANOUT TEE WHERE INDICATED ON DRAWING 2"												
WCO-90017002	WALL CLEANOUT	ROUND STAINLESS STEEL ACCESS COVER COMPLETE WITH SECURITY SCREW, FOR CAST-IRON WALL CLEANOUT TEE WHERE INDICATED ON DRAWING			4"	4"								
RD-90017001	ROOF DRAIN	J.R.SMITH MODEL OR EQUAL 1010 CAST-IRON BODY ROOF DRAIN WITH FLASHING CLAMP, UNDER DECK CLAMP, SUMP RECEIVER CAST IRON DOME. FULL LINE SIZE, SEE												
OD-90017001	OVERFLOW DRAIN	J.R.SMITH MODEL OR EQUAL 1080 WITH HIGH WATER DAM, UNDER DECK CLAMP, SUMP RECEIVER AND CAST IRON DOME. FULL LINE SIZE, SEE PLANS												
DN-90017001	DOWNSPOUT NOZZLE	J.R.SMITH MODEL OR EQUAL 1771-BS CAST BRONZE NOZZLE AND FLANGE, WITH BIRDSCREEN. FULL LINE SIZE, SEE PLANS												
HB-90012001	HOSE BIBB	POLISHED NICKEL BRONZE, INTEGRAL VACUUM BREAKER, LOOSE KEY STOP, ENCLOSED IN A FLUSH MOUNTED WALL BOX. FREEZE PROOF WILL BE PROVIDED. - 3/4"												
HB-90012002	HOSE BIBB	POLISHED NICKEL BRONZE, INTEGRAL VACUUM BREAKER, LOOSE KEY STOP, WALL MOUNTED.												
WM-90012001	WATER METER	2" POSITIVE DISPLACEMENT TYPE WATER METER, CONFORMING TO AWWA C701, SIZED FOR 73 GALLONS PER MINUTE.												
WM-90012002	WATER METER	1-1/2" POSITIVE DISPLACEMENT TYPE WATER METER, CONFORMING TO AWWA C700, SIZED FOR 36 GALLONS PER MINUTE.												
WM-90012003	WATER METER	1" POSITIVE DISPLACEMENT TYPE WATER METER, CONFORMING TO AWWA C700, SIZED FOR 12 GALLONS PER MINUTE.												
ET-90012001	EXPANSION TANK	9.0 GALLON TANK VOLUME WITH 4.25 GALLONS MAXIMUM ACCEPTANCE VOLUME, DIAPHRAGM TYPE, PRE-PRESSURIZED WITH WELDED EXTERIOR, BUTYL DIAPHRAGM 3/4"												
TD-90017001	TRENCH DRAIN	CONCRETE TRENCH DRAIN WITH DUCTILE IRON GRATE, 6" WIDE. SEE STRUCTURAL DRAWINGS FOR EXACT LENGTH AND MORE INFORMATION ON CONCRETE CONSTRUCTION 4" 4"												
PRV-90012001	PRESSURE REDUCING VALVE	2" PRESSURE REDUCING CONTROL GLOBE VALVE W/ FULL PORT, SINGLE CHAMBER VALVE THAT INCORPORATE A ONE-PIECE DISC AND DIAPHRAGM ASSEMBLY, DUCTILE IRON BODY & COVER W/ NSF LISTED FUSION BONDED EPOXY LINED COATING, STAINLESS STEEL STEM, NUT & SPRING, 250 PSI MAXIMUM OPERATING PRESSURE. MINIMUM FLOW RATE OF 6 GPM AND MAXIMUM CONTINUOUS FLOW RATE OF 208 GPM. SET OUTLET PRESSURE AT 115 PSI.												

ELECTRIC WATER HEATER SCHEDULE												
			STORAGE	RECOVERY RATE		ELECTRICAL				EMERGENCY		
MARK	SERVICE TYPE CA		CAPACITY (GAL)	VOLUME/ HOUR (GAL)	TEMP RISE (°F)	kW	V	PHASE	Hz	POWER FOR PHASE 1 (FY17)	BASIS OF DESIGN	
WH-90012001	DOMESTIC HOT WATER	STORAGE TANK	98	96	100	24	460	3	60	NO	A.O. SMITH CUSTOM XI SERIES, MODEL #DSE-80, HEAVY DUTY ELECTRIC COMMERCIAL WATER HEATER	
IWH-90012002	EMERGENCY EYEWASH/ SHOWER	TANKLESS			40	126	460	3	60	NO	KELTECH SNA SERIES SAFETY SHOWER HEATERS	

	HOT WATER RECIRCULATION PUMP SCHEDULE											
MARK	UNIT SERVING	TYPE	CAPACITY (GPM)	TDH (FEET)	ELECTR VOLTS PHA	ICAL DATA		REMARKS				
RCP-90012001	WH-90012001	RECIRCULATION PUMP	8	8	115 1	60 1	/25 NO	INSTALL AS PER MANUFACTURER'S RECOMMENDATIONS.				





RTA

Reference number:

ALL DIMENSIONS AND/OR DIMENSIONS SHOWN IN CALLOUTS/NOTES ARE INCHES UNLESS OTHERWISE NOTED